

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CB-534D XW GCA (2005 OG EFTER)



MOTOR Caterpillar 3054C
Kapacitet: 9 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrisynt LSP 10W-40	Multifleet SHPD 10W-40	

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

HYDRAULISK SYSTEM
Kapacitet: 60 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Gear Oil Alcat 30		

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

ANVEND	KLIMA
Biologisk nedbrydelig olie	Moderat

PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CB-534D XW GCA (2005 OG EFTER)

**KØLESYSTEM**

Kapacitet: 18 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 17*Kontroller alle 10 timer, skift alle 36 måneder/ 6000 timer***EXCENTRISK VÆGTHUS**

Kapacitet: 11,8 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Gearlube HS GL-5 80W-140*Kontroller alle 3 måneder/ 250 timer, skift alle 36 måneder/ 3000 timer***EXCENTRISK VÆGTHUS** Versa Vibe

Kapacitet: 9 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Gearlube HS GL-5 80W-140*Kontroller alle 3 måneder/ 250 timer, skift alle 36 måneder/ 3000 timer***PLANETTRUMLEDREV**

Kapacitet: 2,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Gearlube HS GL-5 80W-140*Kontroller alle 3 måneder/ 250 timer, skift alle 1000 timer*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

PRODUKTANBEFALING 2

Gearlube HS GL-5 80W-140*Skift alle 250 timer/ 6 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.