

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CC34 346 (2008-2013)



MOTOR C2.2

Kapacitet: 10,6 liter

ANVEND

Foretrukket, udvided

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND

Væskeanalyse, foretrukken

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

Kontroller alle 250 timer

ANVEND

Alternativ (acceptabel)

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 250 timer

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 250 timer

CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CC34 346 (2008-2013)



HYDRAULISK SYSTEM

Kapacitet: 48 liter (Hydrauliktank)

ANVEND

Væskeanalyse, bionedbrydelig olie

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

Kontroller alle 12 måneder/ 500 timer

ANVEND

Alternativ (acceptabel)

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

ANVEND

Biologisk nedbrydelig olie

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

ANVEND

Væskeanalyse, alternativ

KLIMA

Moderat

PRODUKTANBEFALING 1

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 12 måneder/ 500 timer

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CC34 346 (2008-2013)



KØLESYSTEM

Kapacitet: 9,3 liter

ANVEND

Væskeanalyse, foretrukken

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 17

Kontroller alle 12 måneder, skift alle 72 måneder/ 12000 timer

ANVEND

Væskeanalyse, indledende (foretrukket)

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 17

Kontroller alle 500 timer

ANVEND

Væskeanalyse, alternativ

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 250 timer

EXCENTRISK VÆGTHUS

Kapacitet: 2,2 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP HD 220

Skift alle 3000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.