

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CS-563C 4KN00001 -> 00928 (1995-2000)



MOTOR 3116T
Kapacitet: 20 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 250 timer/ 3 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Synfleet SHPD 10W-40

PRODUKTANBEFALING 2
Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 250 timer/ 3 måneder

TRANSAXSEL
Kapacitet: 27 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT-Plus

PRODUKTANBEFALING 2
Kroontrak MTH 10W-30

PRODUKTANBEFALING 3
Agrifluid HT

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

HYDRAULISK SYSTEM
Kapacitet: 110 liter (Hydrauliktank)

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Multifleet SCD 30

PRODUKTANBEFALING 2
Gear Oil Alcat 30

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Agrifluid HT-Plus

PRODUKTANBEFALING 3
Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CS-563C 4KN00001 ->

00928 (1995-2000)



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

ANVEND

Mindre krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

PRODUKTANBEFALING 2

Labora Grease

KØLESYSTEM

Kapacitet: 33,1 liter

ANVEND

Foretrukket, udvidet

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 17

Kontroller alle 10 timer, skift alle 72 måneder/ 6000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 24 måneder/ 3000 timer

EXCENTRISK VÆGTHUS

Kapacitet: 55 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube HS GL-5 80W-140

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

CATERPILLAR VIBRATORY COMPACTORS

CB/CC/CD/CP/CS CS-563C 4KN00001 -> 00928 (1995-2000)



SLUTDREV - TROMLE

Kapacitet: 3,2 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gear Oil Alcat 50

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP Synth 220

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

VIBRATORSTØTTE

Kapacitet: 0,85 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

PRODUKTANBEFALING 3

Gearlube HS GL-5 80W-140

Kontroller alle 3 måneder/ 250 timer, skift alle 12 måneder/ 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.