

# CLARK GAFFELTRUCKS, LP-GAS/BENZIN C15 L MITSUBISHI 4G63



**MOTOR** Mitsubishi 4G63  
Kapacitet: 4,8 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Asyntho 5W-30**

*Kontroller alle 10 timer, skift alle 250 timer*

**GEAR** Clark TA-12 1/1  
Kapacitet: 12 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Agrifluid HT-Plus**

*Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer*

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

PRODUKTANBEFALING 1

**Agrifluid HT-Plus**

*Skift alle 50 timer*

**HYDRAULISK SYSTEM**  
Kapacitet: 34 liter (Hydrauliktank)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Perlus H 32**

*Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder*

**HYDRAULISK BREMSESYSTEM**

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Drauliquid DOT 3**

*Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder*

# CLARK GAFFELTRUCKS, LP-GAS/BENZIN C15 L MITSUBISHI 4G63



## SMØREPUNKTER/NIPLER

|                                             |                                                        |                                                     |
|---------------------------------------------|--------------------------------------------------------|-----------------------------------------------------|
| ANVEND<br>Normal                            |                                                        | KLIMA<br>Moderat                                    |
| PRODUKTANBEFALING 1<br><b>Labora Grease</b> | PRODUKTANBEFALING 2<br><b>Q5 MP Calcep Grease EP 2</b> | PRODUKTANBEFALING 3<br><b>MP Lithep Grease EP 2</b> |

## SMØREPUNKTER/NIPLER HJULLEJER

|                                             |                                                        |                                                     |
|---------------------------------------------|--------------------------------------------------------|-----------------------------------------------------|
| ANVEND<br>Normal                            |                                                        | KLIMA<br>Moderat                                    |
| PRODUKTANBEFALING 1<br><b>Labora Grease</b> | PRODUKTANBEFALING 2<br><b>Q5 MP Calcep Grease EP 2</b> | PRODUKTANBEFALING 3<br><b>MP Lithep Grease EP 2</b> |

*Skift alle 2000 timer/ 12 måneder*

## KØLESYSTEM

Kapacitet: 8,5 liter

|                                              |                                             |                                                      |
|----------------------------------------------|---------------------------------------------|------------------------------------------------------|
| ANVEND<br>Normal                             |                                             | KLIMA<br>Moderat                                     |
| PRODUKTANBEFALING 1<br><b>Coolant SP 15+</b> | PRODUKTANBEFALING 2<br><b>Coolant SP 12</b> | PRODUKTANBEFALING 3<br><b>Coolant -38 Organic NF</b> |

*Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*