

**HYDRAULISK SYSTEM**

Kapacitet: 42 liter (Hydrauliktank), Kapacitet: 65 liter (System)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 22*Kontroller alle 2 uger, skift alle 24 måneder***SMØREPUNKTER/NIPLER ANDRE**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2*Skift alle 2 uger***SMØRINGSPUNKTER & NIPLER SVINGGEAR**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2*Skift alle 12 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.