

DITCH WITCH MINISKRIDSTYRING SK SK750 KUBOTA D1105-E3B TIER 4I / STAGE IIIA (2013 OG EFTER)



MOTOR Kubota D1105-E
Kapacitet: 4 liter

ANVEND

Første Service

KLIMA

Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 50 timer

ANVEND

Første Service

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 20W-20

Skift alle 50 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Skift alle 50 timer

ANVEND

Første Service

KLIMA

Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 50 timer

ANVEND

Normalt, svovlniveau i brændstof <0,05 %

KLIMA

Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 10 timer, skift alle 200 timer

ANVEND

Normalt, svovlniveau i brændstof <0,05 %

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 20W-20

Kontroller alle 10 timer, skift alle 200 timer

ANVEND

Normalt, svovlniveau i brændstof <0,05 %

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Kroontrak MTH 10W-30

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 200 timer

DITCH WITCH MINISKRIDSTYRING SK SK750 KUBOTA D1105-E3B TIER 4I / STAGE IIIA (2013 OG EFTER)



ANVEND		KLIMA
Normalt, svovlniveau i brændstof <0,05 %		Arktisk
PRODUKTANBEFALING 1		
Multifleet SCD 10W		
<i>Kontroller alle 10 timer, skift alle 200 timer</i>		

HYDRAULISK SYSTEM		
Kapacitet: 35 liter (Hydrauliktank)		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus
<i>Kontroller alle 10 timer, skift alle 500 timer</i>		

KØLESYSTEM		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
<i>Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.