

DITCH WITCH RETNINGSBOR HT/JT JT100

MACH 1 DEUTZ TCD 2013 L06-2V TIER 3/

EU STAGE IIIA



MOTOR Deutz TCD 2013 L06 2V
Kapacitet: 20 liter

ANVEND

Normalt, svovlniveau i brændstof <0,05 %

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 2

Agrisynth LSP 10W-40

PRODUKTANBEFALING 3

Agridiesel MSP 15W-40

Kontroller alle 10 timer, skift alle 500 timer

UNDERVOGNSTRANSMISSIONSGEARKASSE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 50 timer, skift alle 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 180 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 3

Agrifluid HT-Plus

Kontroller alle 10 timer, skift alle 1000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 42 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

DITCH WITCH RETNINGSBOR HT/JT JT100

MACH 1 DEUTZ TCD 2013 L06-2V TIER 3/

EU STAGE IIIA



ANCHOR GEARKASSE

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 50 timer, skift alle 2000 timer

BOREVÆSKEPLANETGEARKASSE

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 50 timer, skift alle 250 timer

BOREVÆSKEPUMPE

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

ROTATIONSGEARKASSE

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 50 timer, skift alle 1000 timer

SPINDELBREMSE

Kapacitet: 0,15 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 3

Agrifluid HT-Plus

Kontroller alle 50 timer, skift alle 1000 timer

STØDERDREV GEARKASSE

Kapacitet: 0,77 liter (hvert)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 50 timer, skift alle 1000 timer

DITCH WITCH RETNINGSBOR HT/JT JT100

MACH 1 DEUTZ TCD 2013 L06-2V TIER 3/

EU STAGE IIIA



SVINGDREVSGEARKASSE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 500 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.