

DITCH WITCH RETNINGSBOR HT/JT JT20 DEUTZ TD2.9 EPA TIER 4 FINAL/ EU STAGE IV (2014 OG EFTER)



MOTOR Deutz TD 2.9 L04
Kapacitet: 8 liter

ANVEND

Første service, svovlniveau i brændstof > 500 ppm (0,05 %)

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Agrisynth LSP 10W-40

Skift alle 100 timer

ANVEND

Normal, svovlniveau i brændstof <0,0015 %, omgivelsestemperatur >-10° C

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Agrisynth LSP 10W-40

Kontroller alle 10 timer, skift alle 250 timer

UNDERVOGNSTRANSMISSIONSGEARKASSE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 50 timer, skift alle 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 72 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 3

Agrifluid HT-Plus

Kontroller alle 10 timer, skift alle 500 timer

SMØREPUNKTER/-NIPLER DREJEGEARKASSE GLIDNINGS UD GANGSAKSEL

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Compound OGL

PRODUKTANBEFALING 2

Compound OGL EP 0/1

DITCH WITCH RETNINGSBOR HT/JT JT20 DEUTZ TD2.9 EPA TIER 4 FINAL/ EU STAGE IV (2014 OG EFTER)



SMØREPUNKTER/-NIPLER DREJEGEARKASSE INTERNE KILER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Compound OGL	Compound OGL EP 0/1	

Skift alle 1000 timer

KØLESYSTEM

Kapacitet: 17 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Skift alle 2000 timer/ 24 måneder

BOREVÆSKEPUMPE

Kapacitet: 0,9 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

ROTATIONSGEARKASSE

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 50 timer, skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.