

DITCH WITCH RETNINGSBOR HT/JT JT25 CUMMINS QSB4.5 TIER 4I (2013 OG EFTER)



MOTOR Cummins QSB4.5
Kapacitet: 11 liter

ANVEND

Normal, svovlniveau i brændstof <0,0015 %, omgivelsestemperatur >-10° C

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Agrisynth MSP 10W-40

Kontroller alle 10 timer, skift alle 500 timer

UNDERVOGNSTRANSMISSIONSGEARKASSE

Kapacitet: 0-0 liter (Fyldes op til den nedre kant af niveauproppens åbning)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 50 timer, skift alle 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 102 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 3

Agrifluid HT-Plus

Kontroller alle 10 timer, skift alle 1000 timer

KØLESYSTEM

Kapacitet: 22 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Skift alle 2000 timer/ 24 måneder

ANCHOR GEARKASSE

Kapacitet: 0,77 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 50 timer, skift alle 1000 timer

DITCH WITCH RETNINGSBOR HT/JT JT25 CUMMINS QSB4.5 TIER 4I (2013 OG EFTER)

**BOREVÆSKEPUMPE**

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

ROTATIONSGEARKASSE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 50 timer, skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.