

# DOOSAN (DAEWOO) GAFFELTRUCK, DIESEL D/GXD D130S-5 DOOSAN DL06 (TIER III) (2007 OG EFTER)



**MOTOR** Doosan DL06  
Kapacitet: 29 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Agrisynth LSP 10W-40**

PRODUKTANBEFALING 2

**Agrisynth MSP 10W-40**

PRODUKTANBEFALING 3

**Armado Synth 10W-40**

*Skift alle 500 timer/ 3 måneder*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrisynth LSP 10W-40**

PRODUKTANBEFALING 2

**Agrisynth MSP 10W-40**

PRODUKTANBEFALING 3

**Armado Synth 10W-40**

*Skift alle 100 timer*

## DIFFERENTIALE (BAKKEBREMSE)

Kapacitet: 20 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Kontroller alle 1 måneder/ 250 timer, skift alle 9 måneder/ 1500 timer*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 100 timer*

# DOOSAN (DAEWOO) GAFFELTRUCK, DIESEL D/GXD D130S-5 DOOSAN DL06 (TIER III) (2007 OG EFTER)



## GEAR POWERSHIFT ZF 3/3

Kapacitet: 25 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1      |  |  |
|--------------------------|--|--|
| <b>Multifleet SCD 30</b> |  |  |

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

| ANVEND | KLIMA |
|--------|-------|
| Normal | Koldt |

| PRODUKTANBEFALING 1       |  |  |
|---------------------------|--|--|
| <b>Multifleet SCD 10W</b> |  |  |

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

| ANVEND         | KLIMA            |
|----------------|------------------|
| Første Service | Middelhavsagtigt |

| PRODUKTANBEFALING 1      |  |  |
|--------------------------|--|--|
| <b>Multifleet SCD 30</b> |  |  |

Skift alle 100 timer

| ANVEND         | KLIMA |
|----------------|-------|
| Første Service | Koldt |

| PRODUKTANBEFALING 1       |  |  |
|---------------------------|--|--|
| <b>Multifleet SCD 10W</b> |  |  |

Skift alle 100 timer

## NAVREDUKTIONER (BAKKEBREMSE)

Kapacitet: 4,7 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Kontroller alle 1 måneder/ 250 timer, skift alle 9 måneder/ 1500 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 100 timer

# DOOSAN (DAEWOO) GAFFELTRUCK, DIESEL D/GXD D130S-5 DOOSAN DL06 (TIER III) (2007 OG EFTER)



## HYDRAULIKSYSTEM SERVOSTYRING

Kapacitet: 180 liter

| ANVEND              |                     | KLIMA            |
|---------------------|---------------------|------------------|
| Normal              |                     | Middelhavsagtigt |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |                  |
| <b>Perlus H 46</b>  | <b>Perlus H 68</b>  |                  |

Kontroller alle 1 måneder/ 250 timer, skift alle 15 måneder/ 2500 timer

| ANVEND              |                     | KLIMA   |
|---------------------|---------------------|---------|
| Normal              |                     | Moderat |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |         |
| <b>Perlus H 32</b>  | <b>Perlus H 22</b>  |         |

Kontroller alle 1 måneder/ 250 timer, skift alle 15 måneder/ 2500 timer

## KØLESYSTEM

Kapacitet: 35 liter

| ANVEND                |                      | KLIMA                         |
|-----------------------|----------------------|-------------------------------|
| Normal                |                      | Moderat                       |
| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2  | PRODUKTANBEFALING 3           |
| <b>Coolant SP 15+</b> | <b>Coolant SP 12</b> | <b>Coolant -38 Organic NF</b> |

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.