

# DOOSAN (DAEWOO) GAFFELTRUCK, DIESEL D/GXD D50S-5 (2-HASTIGHEDS) HYUNDAI D439E (2009 OG EFTER)



**MOTOR** Hyundai D439E  
Kapacitet: 8,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
|------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
|------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

Skift alle 100 timer

**DRIVAKSEL (VÅD BREMSE)**  
Kapacitet: 14 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2 |  |
|--------------------------|---------------------|--|
| <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b> |  |

Kontroller alle 1 måneder/ 250 timer, skift alle 3 måneder/ 500 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2 |  |
|--------------------------|---------------------|--|
| <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b> |  |

Skift alle 100 timer

**GEAR**  
Kapacitet: 11 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 |  |
|----------------------|---------------------|--|
| <b>SP Matic 2032</b> | <b>ATF Almirol</b>  |  |

Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 |  |
|----------------------|---------------------|--|
| <b>SP Matic 2032</b> | <b>ATF Almirol</b>  |  |

Skift alle 100 timer

# DOOSAN (DAEWOO) GAFFELTRUCK, DIESEL D/GXD D50S-5 (2-HASTIGHEDS) HYUNDAI D439E (2009 OG EFTER)



## KØREAKSEL (BLOKBREMSE)

Kapacitet: 11,3 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Kontroller alle 1 måneder/ 250 timer, skift alle 3 måneder/ 500 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 100 timer

## HYDRAULIKSYSTEM SERVOSTYRING

Kapacitet: 117 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |  |
|---------------------|---------------------|--|
| <b>Perlus H 46</b>  | <b>Perlus H 68</b>  |  |

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |  |
|---------------------|---------------------|--|
| <b>Perlus H 32</b>  | <b>Perlus H 22</b>  |  |

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

## BREMSESYSTEM VÅDE BREMSER

Kapacitet: 0,6 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |  |
|---------------------|---------------------|--|
| <b>Perlus H 32</b>  | <b>Perlus AF 32</b> |  |

Kontroller alle 1 måneder/ 250 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.