

DOOSAN (DAEWOO) GAFFELTRUCKS, LP- GAS/BENZIN G/GC/GX G30G (GX) GM G424F(E) (2008 OG EFTER)



MOTOR GM G424F(E)
Kapacitet: 4,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Dieselfleet MSP 10W-30

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

GEAR Powershift
Kapacitet: 7 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 1000 timer/ 6 måneder

ANVEND
Normal

KLIMA
Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 1000 timer/ 6 måneder

ANVEND
Første Service

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 100 timer

ANVEND
Første Service

KLIMA
Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 100 timer

DOOSAN (DAEWOO) GAFFELTRUCKS, LP-GAS/BENZIN G/GC/GX G30G (GX) GM G424F(E) (2008 OG EFTER)



KØREKSEL (BLOKBREMSE)

Kapacitet: 8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 1 måneder/ 250 timer, skift alle 3 måneder/ 500 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 100 timer

HYDRAULIKSYSTEM SERVOSTYRING

Kapacitet: 44 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus H 68	

Kontroller alle 1 måneder/ 250 timer, skift alle 15 måneder/ 2500 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus H 22	

Kontroller alle 1 måneder/ 250 timer, skift alle 15 måneder/ 2500 timer

BREMSESYSTEM (BLOKBREMSE)

Kapacitet: 0,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Kontroller alle 1 måneder/ 250 timer

DOOSAN (DAEWOO) GAFFELTRUCKS, LP- GAS/BENZIN G/GC/GX G30G (GX) GM G424F(E) (2008 OG EFTER)



KØLESYSTEM

Kapacitet: 9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.