

DOOSAN (DAEWOO) GAFFELTRUCKS, LP- GAS/BENZIN G/GC/GX GC32P-3 MITSUBISHI G430 (2004-2007)



MOTOR Mitsubishi G430
Kapacitet: 4,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Multifleet SHPD 10W-40

Skift alle 50 timer/ 1 uge

DRIVAKSEL (VÅD BREMSE)
Kapacitet: 9,2 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 1000 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 1000 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 50 timer

ANVEND	KLIMA
Første Service	Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 50 timer

DOOSAN (DAEWOO) GAFFELTRUCKS, LP- GAS/BENZIN G/GC/GX GC32P-3 MITSUBISHI G430 (2004-2007)



GEAR Powershift
Kapacitet: 13 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Multifleet SCD 30

Skift alle 1000 timer

ANVEND
Normal

KLIMA
Koldt

PRODUKTANBEFALING 1
Multifleet SCD 10W

Skift alle 1000 timer

ANVEND
Første Service

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Multifleet SCD 30

Skift alle 50 timer/ 1 uge

ANVEND
Første Service

KLIMA
Koldt

PRODUKTANBEFALING 1
Multifleet SCD 10W

Skift alle 50 timer/ 1 uge

DOOSAN (DAEWOO) GAFFELTRUCKS, LP- GAS/BENZIN G/GC/GX GC32P-3 MITSUBISHI G430 (2004-2007)



HYDRAULIKSYSTEEM SERVOSTYRING

Kapaciteit: 34 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus H 68	

Skift alle 1000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 32		

Skift alle 1000 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus H 68	

Skift alle 50 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Perlus H 32		

Skift alle 50 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.