

# DOOSAN (DAEWOO) GRAVEMASKINER MED LARVEBÅND DX, DH DX160HLC DOOSAN DL06 (2008 OG EFTER)



**MOTOR** Doosan DL06  
Kapacitet: 25 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                                   |                             |                             |
|-----------------------------------|-----------------------------|-----------------------------|
| PRODUKTANBEFALING 1               | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3         |
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth LSP 10W-40</b> | <b>Agrisynth MSP 10W-40</b> |

*Kontroller alle 10 timer, skift alle 250 timer*

|                |         |
|----------------|---------|
| ANVEND         | KLIMA   |
| Første Service | Moderat |

|                                   |                             |                             |
|-----------------------------------|-----------------------------|-----------------------------|
| PRODUKTANBEFALING 1               | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3         |
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth LSP 10W-40</b> | <b>Agrisynth MSP 10W-40</b> |

*Skift alle 10 timer*

## HYDRAULISK SYSTEM

Kapacitet: 98,8 liter (Hydrauliktank), Kapacitet: 147,8 liter (System)

|        |                  |
|--------|------------------|
| ANVEND | KLIMA            |
| Normal | Middelhavsagtigt |

|                     |  |  |
|---------------------|--|--|
| PRODUKTANBEFALING 1 |  |  |
| <b>Perlus H 68</b>  |  |  |

*Kontroller alle 10 timer, skift alle 1000 timer*

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                     |                     |  |
|---------------------|---------------------|--|
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 |  |
| <b>Perlus H 46</b>  | <b>Perlus H 32</b>  |  |

*Kontroller alle 10 timer, skift alle 1000 timer*

## SMØREPUNKTER/NIPLER

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                      |                                 |                              |
|----------------------|---------------------------------|------------------------------|
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

# DOOSAN (DAEWOO) GRAVEMASKINER MED LARVEBÅND DX, DH DX160HLC DOOSAN DL06 (2008 OG EFTER)



## KØLESYSTEM

Kapacitet: 20 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

### PRODUKTANBEFALING 2

**Coolant -26**

*Kontroller alle 10 timer, skift alle 2000 timer*

## KØREREDUKTIONSENHED

Kapacitet: 3 liter

### ANVEND

Normal

### KLIMA

Middelhavsagtigt

### PRODUKTANBEFALING 1

**Gearlube GL-5 85W-140**

*Skift alle 1000 timer*

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 1000 timer*

## SVINGREDUKTIONSENHED

Kapacitet: 3,8 liter

### ANVEND

Normal

### KLIMA

Middelhavsagtigt

### PRODUKTANBEFALING 1

**Gearlube GL-5 85W-140**

*Skift alle 1000 timer*

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 1000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.