

DOOSAN (DAEWOO) GRAVEMASKINER MED LARVEBÅND DX, DH DX225NLC DOOSAN DL06 (2006 OG EFTER)



MOTOR Doosan DL06
Kapacitet: 26,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 2

Agrisynth LSP 10W-40

PRODUKTANBEFALING 3

Agrisynth MSP 10W-40

Skift alle 500 timer

SLUTDREV

Kapacitet: 5,4 liter (hvert)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 1000 timer

HYDRAULISK SYSTEM

Kapacitet: 140 liter (Hydrauliktank), Kapacitet: 240 liter (System)

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus H 68

Skift alle 1000 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Perlus H 46

PRODUKTANBEFALING 2

Perlus H 32

Skift alle 1000 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

DOOSAN (DAEWOO) GRAVEMASKINER MED LARVEBÅND DX, DH DX225NLC DOOSAN DL06 (2006 OG EFTER)



KØLESYSTEM

Kapacitet: 24 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 2000 timer

SVINGLEJETS TRÆKENHED

Kapacitet: 5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 1000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.