

DOOSAN (DAEWOO) GRAVEMASKINER MED LARVEBÅND DX, DH DX480LCA DOOSAN DE12TIS TIER II (2013 OG EFTER)



MOTOR Doosan DE12TIS
Kapacitet: 28 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Agrisynth MSP 10W-40

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Agrisynth MSP 10W-40

Skift alle 50 timer

SLUTDREV
Kapacitet: 10 liter (hvert)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Gearlube GL-5 85W-140		

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1		
Gearlube GL-5 85W-140		

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 250 timer/ 6 måneder

DOOSAN (DAEWOO) GRAVEMASKINER MED LARVEBÅND DX, DH DX480LCA DOOSAN DE12TIS TIER II (2013 OG EFTER)



HYDRAULISK SYSTEM

Kapacitet: 265 liter (Hydrauliktank), Kapacitet: 500 liter (System)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus H 68		

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 46	Perlus H 32	

Kontroller alle 10 timer, skift alle 1000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 40 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Skift alle 2000 timer

DOOSAN (DAEWOO) GRAVEMASKINER MED LARVEBÅND DX, DH DX480LCA DOOSAN DE12TIS TIER II (2013 OG EFTER)

**SVINGLEJETS TRÆKENHED**

Kapacitet: 5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140*Kontroller alle 10 timer, skift alle 1000 timer*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Kontroller alle 10 timer, skift alle 1000 timer*

ANVEND

Første Service

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140*Skift alle 250 timer/ 6 måneder*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 250 timer/ 6 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.