

DOOSAN (DAEWOO) GRAVEMASKINER MED LARVEBÅND SOLAR, S-SERIES SOLAR 170 LC-V DAEWOO DB58T (2000-



MOTOR Daewoo DB58T
Kapacitet: 19 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Skift alle 50 timer

HYDRAULISK SYSTEM

Kapacitet: 150 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus H 46		

Skift alle 1000 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
Perlus H 32		

Skift alle 1000 timer

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØREREDUKTIONSENHED

Kapacitet: 3 liter (hvert)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

DOOSAN (DAEWOO) GRAVEMASKINER MED LARVEBÅND SOLAR, S-SERIES SOLAR 170 LC-V DAEWOO DB58T (2000-



LARVEBÅNDSRULLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

SPOR MELLEMHJUL

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Multifleet SCD 30

SVINGREDUKTIONSENHED

Kapacitet: 5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 1000 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 50 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.