

DYNAPAC ASFALTUDLÆGGER MED LARVEBÅND DF/F/SD DF135C DEUTZ TCD 2013 L06 2V (35)



MOTOR Deutz TCD 2013 L06 2V
Kapacitet: 20 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Armado Synth LSP Ultra 10W-40

Kontroller alle 10 timer, skift alle 500 timer

PUMPEREDUKTIONSENHED
Kapacitet: 4,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

HYDRAULISK SYSTEM
Kapacitet: 175 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

ANVEND		KLIMA
Biologisk nedbrydelig olie		Middelhavsagtigt
PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

DYNAPAC ASFALTUDLÆGGER MED LARVEBÅND DF/F/SD DF135C DEUTZ TCD 2013 L06 2V (35)



CENTRAL SMØRINGSENHED		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

SMØREPUNKTER/NIPLER		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

KØLESYSTEM FORBRÆNDINGSMOTOR Kapacitet: 20 liter		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Coolant -38 Organic NF	PRODUKTANBEFALING 2 Coolant -26	PRODUKTANBEFALING 3 Coolant -33 MPG

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

KØREREDUKTIONSENHED Kapacitet: 4 liter		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Abacot MEP 220		

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

SNEKKETYPE II KØREENHED Kapacitet: 2,5 liter		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Abacot MEP 460		

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

DYNAPAC ASFALTUDLÆGGER MED LARVEBÅND DF/F/SD DF135C DEUTZ TCD 2013 L06 2V (35)



SNEKKETYPE II PLANETGEAR

Kapacitet: 0,5 liter (hver side)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 100 timer, skift alle 1000 timer/ 12 måneder

TRANSPORTBÅND GEARKASSE

Kapacitet: 1,5 liter (hver side)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP 220

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.