

# DYNAPAC ASFALTUDLÆGGER MED LARVEBÅND DF/F/SD F1000T CUMMINS QSB-6.7 IIIA/T3 (717) (2011 OG EFTER)



**MOTOR** Cummins QSB6.7C  
Kapacitet: 17,5 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 2  
**Dieselfleet CD+ 15W-40**

Kontroller alle 10 timer, skift alle 250 timer

**PUMPEREDUKTIONSENHED**  
Kapacitet: 5,3 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Gearlube Racing 75W-140**

PRODUKTANBEFALING 2  
**Unigear LS GL-3/GL-5 85W-140**

Kontroller alle 50 timer, skift alle 1000 timer

## HYDRAULISK SYSTEM

Kapacitet: 303 liter, Kapacitet: 189 liter (Hydrauliktank)

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Perlus H 46**

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND  
Biologisk nedbrydelig olie

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1  
**Perlus Biosynth 46**

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

## CENTRAL SMØRINGSSENHED

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**MoS2 Grease EP 2**

# DYNAPAC ASFALTUDLÆGGER MED LARVEBÅND DF/F/SD F1000T CUMMINS QSB-6.7 IIIA/T3 (717) (2011 OG EFTER)



## SMØREPUNKTER/NIPLER

| ANVEND                  |  | KLIMA   |
|-------------------------|--|---------|
| Normal                  |  | Moderat |
| PRODUKTANBEFALING 1     |  |         |
| <b>MoS2 Grease EP 2</b> |  |         |

## KØLESYSTEM MOTOR

Kapacitet: 24,6 liter

| ANVEND                        |                     | KLIMA                  |
|-------------------------------|---------------------|------------------------|
| Normal                        |                     | Moderat                |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3    |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  | <b>Coolant -33 MPG</b> |

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

## KØREREDUKTIONSENHED

Kapacitet: 3 liter (hvert)

| ANVEND                         |                                     | KLIMA   |
|--------------------------------|-------------------------------------|---------|
| Normal                         |                                     | Moderat |
| PRODUKTANBEFALING 1            | PRODUKTANBEFALING 2                 |         |
| <b>Gearlube Racing 75W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |         |

Kontroller alle 250 timer, skift alle 1000 timer

## SNEKKEREDUKTIONSENHED

Kapacitet: 2,5 liter (hvert)

| ANVEND                         |                                     | KLIMA   |
|--------------------------------|-------------------------------------|---------|
| Normal                         |                                     | Moderat |
| PRODUKTANBEFALING 1            | PRODUKTANBEFALING 2                 |         |
| <b>Gearlube Racing 75W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |         |

Kontroller alle 250 timer, skift alle 2000 timer/ 24 måneder

## SNEKKEVINKELGEARKASSE

Kapacitet: 0,6 liter (hver side)

| ANVEND                         |                                     | KLIMA   |
|--------------------------------|-------------------------------------|---------|
| Normal                         |                                     | Moderat |
| PRODUKTANBEFALING 1            | PRODUKTANBEFALING 2                 |         |
| <b>Gearlube Racing 75W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |         |

Kontroller alle 250 timer, skift alle 2000 timer/ 24 måneder

# DYNAPAC ASFALTUDLÆGGER MED LARVEBÅND DF/F/SD F1000T CUMMINS QSB-6.7 IIIA/T3 (717) (2011 OG EFTER)

**TRANSPORTBÅND GEARKASSE**

Kapacitet: 1,5 liter

## ANVEND

Normal

## KLIMA

Moderat

## PRODUKTANBEFALING 1

**Gearlube Racing 75W-140**

## PRODUKTANBEFALING 2

**Unigear LS GL-3/GL-5 85W-140***Kontroller alle 250 timer, skift alle 2000 timer/ 24 måneder*

## ANVEND

Første Service

## KLIMA

Moderat

## PRODUKTANBEFALING 1

**Gearlube Racing 75W-140**

## PRODUKTANBEFALING 2

**Unigear LS GL-3/GL-5 85W-140***Skift alle 100 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*