

DYNAPAC ASFALTUDLÆGGER MED LARVEBÅND DF/F/SD F182CS CUMMINS QSB 6.7-C (758)



MOTOR Cummins QSB6.7C
Kapacitet: 16,7 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Armado Synth LSP Ultra 10W-40

Kontroller alle 10 timer, skift alle 250 timer

HYDRAULISK SYSTEM

Kapacitet: 240 liter (Hydrauliktank)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 68		

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

ANVEND		KLIMA
Biologisk nedbrydelig olie		Middelhavsagtigt
PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

CENTRAL SMØRINGSENHED

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

DYNAPAC ASFALTUDLÆGGER MED LARVEBÅND DF/F/SD F182CS CUMMINS QSB 6.7-C (758)



KØLESYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant SP 15+

PRODUKTANBEFALING 2
Coolant SP 12

PRODUKTANBEFALING 3
Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

KØREREDUKTIONSENHED

Kapacitet: 4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Abacot MEP 220

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

PUMPE TIL FORDELINGSGEAR

Kapacitet: 4,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

SNEKKETYPE I KONISK TANDHJUL

Kapacitet: 0,6 liter (hver side)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Kontroller alle 50 timer, skift alle 2000 timer/ 24 måneder

TRANSPORTBÅND GEARKASSE

Kapacitet: 0,5 liter (hver side)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Abacot MEP 220

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

DYNAPAC ASFALTUDLÆGGER MED LARVEBÅND DF/F/SD F182CS CUMMINS QSB 6.7-C (758)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.