

DYNAPAC ASFALTUDLÆGGER MED LARVEBÅND DF/F/SD SD2500CS CUMMINS QSB 6.7C T3/IIIA TYPE 892/893



MOTOR Cummins QSB6.7C
Kapacitet: 13 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Armado Synth LSP Ultra 10W-40

Kontroller alle 10 timer, skift alle 250 timer

BORKÆDEKASSE
Kapacitet: 4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Abacot MEP 460		

Kontroller alle 100 timer, skift alle 1000 timer/ 12 måneder

PUMPEREDUKTIONSENHED
Kapacitet: 7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

HYDRAULISK SYSTEM
Kapacitet: 240 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 46		

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

ANVEND	KLIMA
Biologisk nedbrydelig olie	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

DYNAPAC ASFALTUDLÆGGER MED LARVEBÅND DF/F/SD SD2500CS CUMMINS QSB 6.7C T3/IIIA TYPE 892/893



SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM MOTOR

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

KØREREDUKTIONSENHED

Kapacitet: 3,5 liter (hver side)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Abacot MEP 220		

Kontroller alle 100 timer, skift alle 1000 timer/ 12 måneder

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1		
Abacot MEP 220		

Skift alle 100 timer

SNEKKEREDUKTIONSENHED

Kapacitet: 1,5 liter (hver side)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Abacot MEP 220		

Kontroller alle 100 timer, skift alle 2000 timer/ 24 måneder

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1		
Abacot MEP 220		

Skift alle 250 timer

DYNAPAC ASFALTUDLÆGGER MED LARVEBÅND DF/F/SD SD2500CS CUMMINS QSB 6.7C T3/IIIA TYPE 892/893

**TRANSPORTBÅND GEARKASSE**

Kapacitet: 1,5 liter (hver side)

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.