

DYNAPAC PLANERINGSMASKINER PL PL600 S CUMMINS QSB5.9



MOTOR Cummins QSB5.9

Kapacitet: 14 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 250 timer

PLANETGEAR DRIVHJUL

Kapacitet: 0,5 liter (hver side)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP 220

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP 220

Skift alle 250 timer

HYDRAULISK SYSTEM

Kapacitet: 130 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus Biosynth 46

PRODUKTANBEFALING 2

Perlus H 46

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

ANVEND

Biologisk nedbrydelig olie

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus Biosynth 46

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

DYNAPAC PLANERINGSMASKINER PL PL600 S CUMMINS QSB5.9



SMØREPUNKTER/NIPLER		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

KØLESYSTEM Kapacitet: 6 liter		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Coolant SP 15+	PRODUKTANBEFALING 2 Coolant SP 12	

Kontroller alle 10 timer, skift alle 1000 timer/ 12 måneder

TROMLEFRÆSERGEARKASSE Kapacitet: 6 liter		
ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Abacot MEP 220		

Kontroller alle 50 timer, skift alle 500 timer

ANVEND Første Service		KLIMA Moderat
PRODUKTANBEFALING 1 Abacot MEP 220		

Skift alle 100 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.