

DYNAPAC RULLER CA134D

10000100X0A009546-> (2012 OG EFTER)



MOTOR John Deere 5030 HF285
Kapacitet: 11,2 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

Skift alle 50 timer

BAGAKSEL TANDSTANGSDREVIHUS
Kapacitet: 0,3 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Gearlube GL-5 85W-140

PRODUKTANBEFALING 2
Unigear LS GL-3/GL-5 85W-140

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

DIFFERENTIALE BAG
Kapacitet: 4,5 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Gearlube GL-5 85W-140

PRODUKTANBEFALING 2
Unigear LS GL-3/GL-5 85W-140

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

DYNAPAC RULLER CA134D**10000100X0A009546-> (2012 OG EFTER)****NAVREDUKTIONER BAG**

Kapacitet: 0,9 liter (hvert)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

*Kontroller alle 1 måneder/ 250 timer, skift alle 6 måneder/ 1000 timer***HYDRAULISK SYSTEM**

Kapacitet: 32 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
Perlus H 68	

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND	KLIMA
Biologisk nedbrydelig olie	Middelhavsagtigt

PRODUKTANBEFALING 1	
Perlus Biosynth 46	

*Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder***SMØREPUNKTER/NIPLER**

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 10 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Coolant -38 Organic NF	Coolant -26

DYNAPAC RULLER CA134D

10000100X0A009546-> (2012 OG EFTER)



TROMLE

Kapacitet: 6,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 1 måneder/ 250 timer, skift alle 12 måneder/ 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.