

DYNAPAC RULLER CC324HF

10000315X0A000001-> (2011 OG EFTER)



MOTOR Cummins QSB3.3
Kapacitet: 7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Skift alle 50 timer

HYDRAULISK SYSTEM
Kapacitet: 40 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 68		

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND	KLIMA
Biologisk nedbrydelig olie	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

DYNAPAC RULLER CC324HF

10000315X0A000001-> (2011 OG EFTER)

**KØLESYSTEM**

Kapacitet: 20,1 liter, Kapacitet: 18,6 liter (Uten hytte)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Kontroller alle 500 timer/ 12 måneder, skift alle 24 måneder***TROMLE**

Kapacitet: 14 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP HD 150

PRODUKTANBEFALING 2

Abacot MEP 150*Kontroller alle 3 måneder/ 500 timer, skift alle 6 måneder/ 1000 timer***TRUMLEDREVENHED**

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140*Kontroller alle 50 timer, skift alle 6 måneder/ 1000 timer*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Kontroller alle 50 timer, skift alle 6 måneder/ 1000 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.