

# DYNAPAC RULLER CG233HF 86110300-86110399 (2006-2011)



**MOTOR** Deutz BF4M-2011  
Kapacitet: 18 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
|-------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
|-------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Skift alle 50 timer

**HYDRAULISK SYSTEM**  
Kapacitet: 38 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>Perlus H 68</b>  |  |  |

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

| ANVEND                     | KLIMA            |
|----------------------------|------------------|
| Biologisk nedbrydelig olie | Middelhavsagtigt |

| PRODUKTANBEFALING 1       |  |  |
|---------------------------|--|--|
| <b>Perlus Biosynth 46</b> |  |  |

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

**SMØREPUNKTER/NIPLER**

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
|----------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

# DYNAPAC RULLER CG233HF 86110300-86110399 (2006-2011)



## TROMLE

Kapacitet: 13 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Abacot MEP HD 150**

### PRODUKTANBEFALING 2

**Abacot MEP 150**

*Kontroller alle 3 måneder/ 500 timer, skift alle 12 måneder/ 2000 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*