

DYNAPAC TROMLER MED GUMMIHJUL CP CP132 CUMMINS 4BT3.9 (*21620331* ->)



MOTOR Cummins 4BT 3.9
Kapacitet: 9,5 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 1 måneder/ 250 timer

HYDRAULISK SYSTEM

Kapacitet: 100 liter (Hydrauliksystem inkl. tank), Kapacitet: 75 liter (Hydrauliktank)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 68

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND
Biologisk nedbrydelig olie

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Perlus Biosynth 46

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
HT Q9 High Grade Grease

PRODUKTANBEFALING 2
Labora Grease

KØLESYSTEM

Kapacitet: 20 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant -38 Organic NF

PRODUKTANBEFALING 2
Coolant -26

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.