

# DYNAPAC VIBRATORROMLE MED ÉN TROMLE CA CA262 CUMMINS QSB 6.7C (10000112X0A000001 ->)



**MOTOR** Cummins QSB6.7C  
Kapacitet: 14 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                               |                               |                               |
|-------------------------------|-------------------------------|-------------------------------|
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

|                |         |
|----------------|---------|
| ANVEND         | KLIMA   |
| Første Service | Moderat |

|                               |                               |                               |
|-------------------------------|-------------------------------|-------------------------------|
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Skift alle 50 timer

**DIFFERENTIALE BAG**  
Kapacitet: 12 liter

|        |                  |
|--------|------------------|
| ANVEND | KLIMA            |
| Normal | Middelhavsagtigt |

|                              |                                     |  |
|------------------------------|-------------------------------------|--|
| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2                 |  |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

Kontroller alle 250 timer, skift alle 6 måneder/ 1000 timer

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                             |                                    |  |
|-----------------------------|------------------------------------|--|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Kontroller alle 250 timer, skift alle 6 måneder/ 1000 timer

**NAVREDUKTIONER BAG**  
Kapacitet: 1,85-2 liter (hvert nav)

|        |                  |
|--------|------------------|
| ANVEND | KLIMA            |
| Normal | Middelhavsagtigt |

|                              |                                     |  |
|------------------------------|-------------------------------------|--|
| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2                 |  |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

Kontroller alle 250 timer, skift alle 6 måneder/ 1000 timer

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                             |                                    |  |
|-----------------------------|------------------------------------|--|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Kontroller alle 250 timer, skift alle 6 måneder/ 1000 timer

# DYNAPAC VIBRATORROMLE MED ÉN TROMLE CA CA262 CUMMINS QSB 6.7C (10000112X0A000001 ->)



## HYDRAULISK SYSTEM

Kapacitet: 75 liter (Hydrauliksystem inkl. tank), Kapacitet: 52 liter (Hydrauliktank)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>Perlus H 68</b>  |  |  |

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

| ANVEND                     | KLIMA            |
|----------------------------|------------------|
| Biologisk nedbrydelig olie | Middelhavsagtigt |

| PRODUKTANBEFALING 1       |  |  |
|---------------------------|--|--|
| <b>Perlus Biosynth 46</b> |  |  |

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

## SMØREPUNKTER/NIPLER

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1            | PRODUKTANBEFALING 2  |  |
|--------------------------------|----------------------|--|
| <b>HT Q9 High Grade Grease</b> | <b>Labora Grease</b> |  |

## KØLESYSTEM

Kapacitet: 29 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |  |
|-------------------------------|---------------------|--|
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |  |

## LEDKOBLING

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1             | PRODUKTANBEFALING 2          |  |
|---------------------------------|------------------------------|--|
| <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |  |

# DYNAPAC VIBRATORROMLE MED ÉN TROMLE CA CA262 CUMMINS QSB 6.7C (10000112X0A000001 ->)



## TROMLE

Kapacitet: 15 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Abacot MEP HD 150**

Kontroller alle 250 timer, skift alle 2000 timer/ 12 måneder

### ANVEND

Første Service

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Abacot MEP HD 150**

Skift alle 50 timer

## TROMLE GEARKASSE

Kapacitet: 3 liter

### ANVEND

Normal

### KLIMA

Middelhavsagtigt

### PRODUKTANBEFALING 1

**Gearlube GL-5 85W-140**

### PRODUKTANBEFALING 2

**Unigear LS GL-3/GL-5 85W-140**

Kontroller alle 250 timer, skift alle 2000 timer/ 12 måneder

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

### PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

Kontroller alle 250 timer, skift alle 2000 timer/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.