

DYNAPAC VIBRATORROMLE MED ÉN TROMLE CA CA2800 D CUMMINS T4I/IIIB (10000142X0A00XXXX ->)



MOTOR Cummins QSB4.5
Kapacitet: 11 liter

ANVEND

Alternativ, svovlniveau i brændstof < 0,0015 %

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth MSP 10W-40

PRODUKTANBEFALING 2

Agridiesel MSP 15W-40

PRODUKTANBEFALING 3

Dieselfleet MSP 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

DIFFERENTIALE BAG

Kapacitet: 16,5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

NAVREDUKTIONER

Kapacitet: 1,7 liter (hvert nav)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

DYNAPAC VIBRATORROMLE MED ÉN TROMLE CA CA2800 D CUMMINS T4I/IIIB (10000142X0A00XXXX ->)



TROMLEPATRON

Kapacitet: 2,2 liter (hver side)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP HD 150

Kontroller alle 250 timer, skift alle 2000 timer/ 24 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP HD 150

Skift alle 50 timer

HYDRAULISK SYSTEM

Kapacitet: 80 liter (Hydrauliksystem inkl. tank), Kapacitet: 41 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 68

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

ANVEND

Biologisk nedbrydelig olie

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Perlus Biosynth 46

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

PRODUKTANBEFALING 2

Labora Grease

KØLESYSTEM MOTOR

Kapacitet: 24-26,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 24 måneder

DYNAPAC VIBRATORROMLE MED ÉN TROMLE CA CA2800 D CUMMINS T4I/IIIB (10000142X0A00XXXX ->)

**TROMLE GEARKASSE**

Kapacitet: 2,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Skift alle 50 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 50 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.