

# DYNAPAC VIBRATORROMLE MED ÉN TROMLE CA CA3500 D/PD CUMMINS T3/IIIA (10000145X0A009674 ->)



**MOTOR** Cummins QSB4.5 (IIIA/T3)  
Kapacitet: 11 liter

| ANVEND                                         | KLIMA   |
|------------------------------------------------|---------|
| Alternativ, svovlniveau i brændstof < 0,0015 % | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2          | PRODUKTANBEFALING 3           |
|-----------------------------|------------------------------|-------------------------------|
| <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> | <b>Dieselfleet MSP 15W-40</b> |

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

**DIFFERENTIALE BAG**  
Kapacitet: 16,5 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2                 |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

**NAVREDUKTIONER**  
Kapacitet: 1,7 liter (hvert nav)

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2                 |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

# DYNAPAC VIBRATORTROMLE MED ÉN TROMLE CA CA3500 D/PD CUMMINS T3/IIIA (10000145X0A009674 ->)



## TROMLEPATRON

Kapacitet: 2,2 liter (hver side)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Abacot MEP HD 150**

Kontroller alle 250 timer, skift alle 2000 timer/ 24 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

**Abacot MEP HD 150**

Skift alle 50 timer

## HYDRAULISK SYSTEM

Kapacitet: 80 liter (Hydrauliksystem inkl. tank), Kapacitet: 41 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Perlus H 68**

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

ANVEND

Biologisk nedbrydelig olie

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

**Perlus Biosynth 46**

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

## SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**HT Q9 High Grade Grease**

PRODUKTANBEFALING 2

**Labora Grease**

## KØLESYSTEM MOTOR

Kapacitet: 24-26,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

PRODUKTANBEFALING 2

**Coolant -26**

Skift alle 24 måneder

# DYNAPAC VIBRATORTROMLE MED ÉN TROMLE CA CA3500 D/PD CUMMINS T3/IIIA (10000145X0A009674 ->)



## TROMLE GEARKASSE

Kapacitet: 2,5 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2                 |
|------------------------------|-------------------------------------|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

| ANVEND         | KLIMA            |
|----------------|------------------|
| Første Service | Middelhavsagtigt |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2                 |
|------------------------------|-------------------------------------|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |

Skift alle 50 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Skift alle 50 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.