

# DYNAPAC VIBRATORROMLE MED TO TROMLER CC/CG/LA CC12-SERIE 2 DEUTZ F2L-511



**MOTOR** Deutz F2L-511  
Kapacitet: 3,5 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           |  |
|-------------------------------|-------------------------------|--|
| <b>Multifleet SHPD 10W-40</b> | <b>Multifleet SHPD 15W-40</b> |  |

*Skift alle 200 timer*

| ANVEND         | KLIMA            |
|----------------|------------------|
| Første Service | Middelhavsagtigt |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           |  |
|-------------------------------|-------------------------------|--|
| <b>Multifleet SHPD 10W-40</b> | <b>Multifleet SHPD 15W-40</b> |  |

*Skift alle 50 timer*

**HYDRAULISK SYSTEM**  
Kapacitet: 77 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>Perlus H 68</b>  |  |  |

*Kontroller alle 10 timer, skift alle 6 måneder/ 1000 timer*

## SMØREPUNKTER/NIPLER

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
|----------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

**TRUMLE BAG**  
Kapacitet: 19 liter

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Kontroller alle 50 timer, skift alle 12 måneder/ 2000 timer*

# DYNAPAC VIBRATORROMLE MED TO TROMLER CC/CG/LA CC12-SERIE 2 DEUTZ F2L-511



**TRUMLE FOR**  
Kapacitet: 19 liter

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Kontroller alle 50 timer, skift alle 12 måneder/ 2000 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*