

DYNAPAC VIBRATOR TROMLE MED TO TROMLER CC/CG/LA CC1200 KUBOTA D1703 IIIB/T4I (10000363X0A013590 ->)



MOTOR Kubota D1703-M
Kapacitet: 7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrisynth MSP 10W-40

PRODUKTANBEFALING 2
Agridiesel MSP 15W-40

PRODUKTANBEFALING 3
Dieselfleet MSP 15W-40

Kontroller alle 10 timer, skift alle 250 timer

HYDRAULISK SYSTEM
Kapacitet: 45 liter (Hydrauliktank)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 68

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND
Biologisk nedbrydelig olie

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Perlus Biosynth 46

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
HT Q9 High Grade Grease

PRODUKTANBEFALING 2
Labora Grease

KØLESYSTEM
Kapacitet: 5,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant -38 Organic NF

PRODUKTANBEFALING 2
Coolant -26

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

DYNAPAC VIBRATOR TROMLE MED TO TROMLER CC/CG/LA CC1200 KUBOTA D1703 IIB/T4I (10000363X0A013590 ->)



TROMLE

Kapacitet: 4 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 3 måneder/ 500 timer, skift alle 12 måneder/ 2000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 3 måneder/ 500 timer, skift alle 12 måneder/ 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.