

DYNAPAC VIBRATORROMLE MED TO TROMLER CC/CG/LA CC21 SERIE 1 DEUTZ F4L-912 (489 18 57 ->)



MOTOR Deutz F4L-912
Kapacitet: 9,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Multifleet SHPD 15W-40

Skift alle 200 timer

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
Multifleet SHPD 15W-40

Skift alle 50 timer

PUMPEREDUKTIONSENHED
Kapacitet: 1,5-3,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Kontroller alle 200 timer, skift alle 12 måneder/ 2000 timer

TROMLEGEARKASSE BAG

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Kontroller alle 50 timer, skift alle 3 måneder/ 500 timer

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Skift alle 200 timer

DYNAPAC VIBRATORROMLE MED TO TROMLER CC/CG/LA CC21 SERIE 1 DEUTZ F4L-912 (489 18 57 ->)



TROMLEGEARKASSE FOR

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 50 timer, skift alle 3 måneder/ 500 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 200 timer

HYDRAULISK SYSTEM

Kapacitet: 140 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus H 68		

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

BREMSEHUS (PÅ BAGTROMLE) Renondin

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus H 22		

Skift alle 200 timer

TRUMLE BAG

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 50 timer, skift alle 12 måneder/ 2000 timer

DYNAPAC VIBRATORROMLE MED TO TROMLER CC/CG/LA CC21 SERIE 1 DEUTZ F4L-912 (489 18 57 ->)



TRUMLE FOR
Kapacitet: 20 liter

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 50 timer, skift alle 12 måneder/ 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.