

# DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC2300 (60 KW) CUMMINS QSB 3.3 T3/IIIA



**ENGINE Cummins QSB3.3**  
Capacity: 7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|-------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Check every 10 hours, change every 1 months/ 250 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|-------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Change every 50 hours*

## HYDRAULIC SYSTEM

Capacity: 40 liter (Hydraulic tank)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Perlus H 68</b>       |  |  |

*Check every 10 hours, change every 2000 hours/ 12 months*

| USE               | CLIMATE       |
|-------------------|---------------|
| Biodegradable oil | Mediterranean |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Perlus Biosynth 46</b> |  |  |

*Check every 10 hours, change every 2000 hours/ 12 months*

## GREASE POINTS/NIPPLES

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2 |  |
|--------------------------------|--------------------------|--|
| <b>HT Q9 High Grade Grease</b> | <b>Labora Grease</b>     |  |

# DYNAPAC TANDEM DRUM VIBRATORY ROLLERS CC/CG/LA CC2300 (60 KW) CUMMINS QSB 3.3 T3/IIIA

**COOLING SYSTEM**

Capacity: 18,6-19,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |  |
|-------------------------------|--------------------------|--|
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |  |

*Change every 24 months***DRUM**

Capacity: 6,4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Abacot MEP HD 150</b> |  |  |

*Check every 3 months/ 500 hours, change every 6 months/ 1000 hours***DRUM GEARBOX**

Capacity: 1,7 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

*Check every 50 hours, change every 6 months/ 1000 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Check every 50 hours, change every 6 months/ 1000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.