

DYNAPAC VIBRATORROMLE MED TO TROMLER CC/CG/LA CC424HF (113 KW) CUMMINS QSB 4.5 IIIA/T3



MOTOR Cummins QSB4.5 (IIIA/T3)
Kapacitet: 11 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

HYDRAULISK SYSTEM
Kapacitet: 40 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND	KLIMA
Biologisk nedbrydelig olie	Moderat

PRODUKTANBEFALING 1		
Perlus H 68		

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
HT Q9 High Grade Grease	Labora Grease	

KØLESYSTEM
Kapacitet: 21,4-23,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Skift alle 24 måneder

TROMLE
Kapacitet: 14 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

DYNAPAC VIBRATORTROMLE MED TO TROMLER CC/CG/LA CC424HF (113 KW) CUMMINS QSB 4.5 IIIA/T3

**TROMLEGEARKASSE**

Kapacitet: 1,5 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

ANVEND		KLIMA
Første Service		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Skift alle 50 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 50 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.