

DYNAPAC VIBRATOR TROMLE MED TO TROMLER CC/CG/LA CC424HF (93 KW) CUMMINS QSB 4.5 (10000320X0A000001 ->)



MOTOR Cummins QSB4.5
Kapacitet: 11 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

HYDRAULISK SYSTEM
Kapacitet: 40 liter (Hydrauliktank)

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Perlus Biosynth 46

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

ANVEND
Biologisk nedbrydelig olie

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 68

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
HT Q9 High Grade Grease

PRODUKTANBEFALING 2
Labora Grease

KØLESYSTEM
Kapacitet: 21,4-23,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant -38 Organic NF

PRODUKTANBEFALING 2
Coolant -26

Skift alle 24 måneder

DYNAPAC VIBRATORROMLE MED TO TROMLER CC/CG/LA CC424HF (93 KW) CUMMINS QSB 4.5 (10000320X0A000001 ->)

**TROMLE**

Kapacitet: 14 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Abacot MEP HD 150*Kontroller alle 3 måneder/ 500 timer, skift alle 6 måneder/ 1000 timer***TROMLE GEARKASSE**

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140*Kontroller alle 50 timer, skift alle 6 måneder/ 1000 timer*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Kontroller alle 50 timer, skift alle 6 måneder/ 1000 timer*

ANVEND

Første Service

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140*Skift alle 50 timer*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 50 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.