

# DYNAPAC VIBRATORROMLE MED TO TROMLER CC/CG/LA CC432 CUMMINS 4BTAA 3.9C (\*42720433\* ->) (2003-2008)



**MOTOR** Cummins 4BTAA 3.9C  
Kapacitet: 11 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
|-------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Kontroller alle 10 timer, skift alle 3 måneder/ 500 timer

**PUMPEREDUKTIONSENHED**  
Kapacitet: 0,8 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Kontroller alle 50 timer, skift alle 6 måneder/ 1000 timer

**HYDRAULISK SYSTEM**  
Kapacitet: 40 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>Perlus H 68</b>  |  |  |

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

| ANVEND                     | KLIMA            |
|----------------------------|------------------|
| Biologisk nedbrydelig olie | Middelhavsagtigt |

| PRODUKTANBEFALING 1       |  |  |
|---------------------------|--|--|
| <b>Perlus Biosynth 46</b> |  |  |

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

**SMØREPUNKTER/NIPLER**

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1            | PRODUKTANBEFALING 2  |  |
|--------------------------------|----------------------|--|
| <b>HT Q9 High Grade Grease</b> | <b>Labora Grease</b> |  |

# DYNAPAC VIBRATOR TROMLE MED TO TROMLER CC/CG/LA CC432 CUMMINS 4BTAA 3.9C (\*42720433\* ->) (2003-2008)



## KØLESYSTEM

Kapacitet: 7,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

PRODUKTANBEFALING 2

**Coolant -26**

*Skift alle 2000 timer/ 24 måneder*

## LEDKOBLING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 2

**MP Lithep Grease EP 2**

*Skift alle 50 timer*

## TROMLE

Kapacitet: 6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Abacot MEP HD 150**

*Kontroller alle 3 måneder/ 500 timer, skift alle 6 måneder/ 1000 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*