

# DYNAPAC VIBRATORROMLE MED TO TROMLER CC/CG/LA CC624HF (119 KW) CUMMINS QSB 4.5 IIB/T4I



## MOTOR Cummins QSB4.5 (IIB/T4I)

Kapacitet: 11 liter

| ANVEND                                  |                              | KLIMA                         |
|-----------------------------------------|------------------------------|-------------------------------|
| Normal, svovlniveau i brændstof <15 ppm |                              | Moderat                       |
| PRODUKTANBEFALING 1                     | PRODUKTANBEFALING 2          | PRODUKTANBEFALING 3           |
| <b>Agrisynth MSP 10W-40</b>             | <b>Agridiesel MSP 15W-40</b> | <b>Dieselfleet MSP 15W-40</b> |

Kontroller alle 10 timer, skift alle 500 timer/ 6 måneder

## HYDRAULISK SYSTEM

Kapacitet: 40 liter (Hydrauliktank)

| ANVEND                    |  | KLIMA            |
|---------------------------|--|------------------|
| Normal                    |  | Middelhavsagtigt |
| PRODUKTANBEFALING 1       |  |                  |
| <b>Perlus Biosynth 46</b> |  |                  |

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

| ANVEND                     |  | KLIMA   |
|----------------------------|--|---------|
| Biologisk nedbrydelig olie |  | Moderat |
| PRODUKTANBEFALING 1        |  |         |
| <b>Perlus H 68</b>         |  |         |

Kontroller alle 10 timer, skift alle 2000 timer/ 12 måneder

## SMØREPUNKTER/NIPLER

| ANVEND                         |                      | KLIMA   |
|--------------------------------|----------------------|---------|
| Normal                         |                      | Moderat |
| PRODUKTANBEFALING 1            | PRODUKTANBEFALING 2  |         |
| <b>HT Q9 High Grade Grease</b> | <b>Labora Grease</b> |         |

## KØLESYSTEM

Kapacitet: 21,4-23,6 liter

| ANVEND                        |                     | KLIMA   |
|-------------------------------|---------------------|---------|
| Normal                        |                     | Moderat |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |         |

Skift alle 24 måneder

## TROMLE

Kapacitet: 17 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

# DYNAPAC VIBRATORROMLE MED TO TROMLER CC/CG/LA CC624HF (119 KW) CUMMINS QSB 4.5 IIB/T4I



## TROMLEGEARKASSE

Kapacitet: 1,5 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2                 |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Kontroller alle 50 timer, skift alle 1000 timer/ 12 måneder

| ANVEND         | KLIMA            |
|----------------|------------------|
| Første Service | Middelhavsagtigt |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2                 |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

Skift alle 50 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 50 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.