

ECOLOG HØSTERE 550D OM906LA (2009-2013)



MOTOR Mercedes-Benz OM906LA
Kapacitet: 24-29 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP 10W-40	Armado Synth 10W-40	Synfleet SHPD 10W-40

BOGIE-TRÆKENHED
Kapacitet: 22 liter (hvert)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

NAVREDUKTIONER
Kapacitet: 5 liter (hvert)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

HYDRAULISK SYSTEM
Kapacitet: 234 liter (Hydrauliktank), Kapacitet: 440 liter (Total)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus Biosynth 46		

ECOLOG HØSTERE 550D OM906LA (2009-2013)



HYDRAULISK TIPPESTYSTEM FOR KABINEN

Kapacitet: 1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus Biosynth 46		

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
Gear Grease EP 1		

SMØREPUNKTER/NIPLER CENTRALSMØRESYSTEM

Kapacitet: 2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
Gear Grease EP 1		

KØLESYSTEM

Kapacitet: 50 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant SP 11

ECOLOG HØSTERE 550D OM906LA (2009-2013)



PUMPEDREV

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.