

ETEC GRAVEMASKINER MED LARVEBÅND

802-II



MOTOR Mitsubishi L3E
Kapacitet: 4,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak CVT 10W-40

PRODUKTANBEFALING 2
Agrisynth MSP 10W-40

PRODUKTANBEFALING 3
Agridiesel MSP 15W-40

HYDRAULISK SYSTEM
Kapacitet: 26 liter (Hydrauliktank)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Perlus H 46

PRODUKTANBEFALING 2
Perlus H 32

Skift alle 1000 timer

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Labora Grease

PRODUKTANBEFALING 2
Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3
MP Lithep Grease EP 2

KØLESYSTEM
Kapacitet: 1,8 liter (Radiator)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant SP 15+

PRODUKTANBEFALING 2
Coolant SP 12

PRODUKTANBEFALING 3
Coolant -38 Organic NF

KØREREDUKTIONSENHED
Kapacitet: 0,33 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-5 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Skift alle 500 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.