

FIAT-KOBELCO GUMMIHJULSLÆSSERE W110E IVECO NEF4TAA-4502 TIER 2 (2003- 2005)



MOTOR Iveco NEF 4 TAA-4502 Tier 2
Kapacitet: 12,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Armado Synth 5W-30

Skift alle 250 timer/ 6 måneder

DIFFERENTIALE BAG

Kapacitet: 22 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Skift alle 2000 timer

DIFFERENTIALE FOR

Kapacitet: 22 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Skift alle 2000 timer

GEAR POWERSHIFT 4/3

Kapacitet: 18,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Synfleet SHPD 10W-40	Armado Synth 5W-30	Multifleet SHPD 10W-40

Skift alle 1000 timer

FIAT-KOBELCO GUMMIHJULSLÆSSERE W110E IVECO NEF4TAA-4502 TIER 2 (2003- 2005)



HYDRAULISK SYSTEM

Kapacitet: 63 liter (Tank), Kapacitet: 114 liter (Total)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

Skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

KØLESYSTEM

Kapacitet: 22 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.