

FIAT-KOBELCO GUMMIHJULSLÆSSERE W270E CUMMINS QSM11 (2002-2005)



MOTOR Cummins QSM11
Kapacitet: 34 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 2
Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3
Multifleet SHPD 15W-40

Skift alle 250 timer/ 6 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Synfleet SHPD 10W-40

PRODUKTANBEFALING 2
Multifleet SHPD 10W-40

Skift alle 250 timer/ 6 måneder

DIFFERENTIALE BAG
Kapacitet: 46 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube Racing 75W-140

PRODUKTANBEFALING 2
Unigear LS GL-3/GL-5 85W-140

Skift alle 2000 timer

DIFFERENTIALE FOR
Kapacitet: 46 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube Racing 75W-140

PRODUKTANBEFALING 2
Unigear LS GL-3/GL-5 85W-140

Skift alle 2000 timer

GEAR POWERSHIFT 4/4
Kapacitet: 32 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Synfleet SHPD 10W-40

PRODUKTANBEFALING 2
Multifleet SHPD 10W-40

Skift alle 1000 timer

FIAT-KOBELCO GUMMIHJULSLÆSSERE W270E CUMMINS QSM11 (2002-2005)



HYDRAULISK SYSTEM

Kapacitet: 165 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 46

Skift alle 2000 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

KØLESYSTEM

Kapacitet: 43 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.