

GEHL GRAVEMASKINER MED LARVEBÅND

MB/Z 803 TIER 3, AH00611 - (2004-2011)



MOTOR Yanmar 4TNV98
Kapacitet: 10,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Armado Synth 10W-40

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Armado Synth 10W-40

Skift alle 50 timer

KØREREDUKTIONSENHEDER
Kapacitet: 1,3 liter (hvert)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 50 timer, skift alle 1000 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 50 timer

HYDRAULISK SYSTEM
Kapacitet: 99 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus Biosynth 46	Perlus H 46	

Kontroller alle 10 timer, skift alle 1000 timer

ANVEND	KLIMA
Biologisk nedbrydelig olie	Moderat

PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Kontroller alle 10 timer, skift alle 1000 timer

GEHL GRAVEMASKINER MED LARVEBÅND

MB/Z 803 TIER 3, AH00611 - (2004-2011)



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

Kontroller alle 10 timer

KØLESYSTEM

Kapacitet: 7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 1000 timer

DREJERING TANDHJUL

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

HT Q9 High Grade Grease

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.