GEHL TRACKED EXCAVATORS MB/Z Z35 GEN2 YANMAR 3TNV88F-ESBV TIER 4 (S/N 00701 ->) (2012 AND AFTER)



ENGINE Yanmar 3TNV88F
Capacity: 7,3 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40

Change every 500 hours/ 12 months

Normal Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

CLIMATE
Cold

Multifleet SCD 10W

Change every 500 hours/ 12 months

Initial service

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40

Change every 50 hours

Initial service Cold

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

CLIMATE
COID

COID

Change every 50 hours

TRAVEL REDUCTION UNITS Capacity: 0,5 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 1000 hours/12 months

Change every 100 hours	Onigear H3 GL-3/GL-3 80VV-90	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Initial service		Moderate
USE		CLIMATE

GEHL TRACKED EXCAVATORS MB/Z Z35 GEN2 YANMAR 3TNV88F-ESBV TIER 4 (S/N 00701 ->) (2012 AND AFTER)



HYDRAULIC SYSTEM
Capacity: 54 liter (Hydraulic system including tank), Capacity: 36 liter (Hydraulic tank)

USE

Normal

PRODUCT RECOMMENDATION 1

Perlus HCD 46

Change every 1000 hours

GREASE POINTS/NIPPLES				
use Normal		climate Moderate		
			PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

COOLING SYSTEM Capacity: 4,4 liter (Radiator)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15	Coolant SP 15+	Coolant SP 12
Change every 1000 hours/ 12 mon	ths	1

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.