

GEHL GUMMIHJULSLÆSSERE AL/AWS/HL/KL KL-405 (GEHLMAX) PERKINS 104-19 (1993-1994)



MOTOR Perkins 104-19

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

Skift alle 200 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

Skift alle 50 timer

DIFFERENTIALE BAG

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 600 timer/ 12 måneder

DIFFERENTIALE FOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 600 timer/ 12 måneder

NAVREDUKTIONER BAG

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 600 timer/ 12 måneder

GEHL GUMMIHJULSLÆSSERE AL/AWS/HL/KL KL-405 (GEHLMAX) PERKINS 104-19 (1993-1994)



NAVREDUKTIONER FOR

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 600 timer/ 12 måneder*

HYDRAULISK SYSTEM HYDROSTATISK DREV

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

ATF-A*Skift alle 600 timer/ 12 måneder*

HYDRAULISK BREMSESYSTEM

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SMØREPUNKTER/NIPLER

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.