

GEHL LÆSSEMASKINERR MED KOMPAKT SPORVIDDE RT/CTL RT175 GEN:2 YANMAR 4TNV98-ZNMS TIER 4 (S/N 811001 - 811700)



MOTOR Yanmar 4TNV98
Kapacitet: 10,4 liter

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Skift alle 50 timer

ANVEND	KLIMA
Alternativ, svovlniveau i brændstof < 0,0015 %	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Skift alle 250 timer/ 6 måneder

KØREREDUKTIONSENHEDER
Kapacitet: 0,9-1,1 liter (hvert)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Skift alle 1000 timer/ 12 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Skift alle 150 timer/ 4 måneder

HYDRAULISK SYSTEM

Kapacitet: 70 liter (Hydrauliksystem inkl. tank), Kapacitet: 41,6 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus HCD 46		

Skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Biologisk nedbrydelig olie	Moderat

PRODUKTANBEFALING 1		
Perlus Biosynth 46		

Skift alle 500 timer/ 12 måneder

GEHL LÆSSEMASKINERR MED KOMPAKT SPORVIDDE RT/CTL RT175 GEN:2 YANMAR 4TNV98-ZNMS TIER 4 (S/N 811001 - 811700)



SMØREPUNKTER/INFLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 13,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Skift alle 500 timer/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.