

# GEHL LÆSSEMASKINERR MED KOMPAKT SPORVIDDE RT/CTL RT175 YANMAR 4TNV98-ZNMS TIER 4I (S/N 10721 - 811000)



**MOTOR** Yanmar 4TNV98  
Kapacitet: 10,4 liter

| ANVEND                                  | KLIMA   |
|-----------------------------------------|---------|
| Normal, svovlniveau i brændstof <0,05 % | Moderat |

| PRODUKTANBEFALING 1               | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3          |
|-----------------------------------|-----------------------------|------------------------------|
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> |

Skift alle 250 timer/ 6 måneder

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1               | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3          |
|-----------------------------------|-----------------------------|------------------------------|
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth MSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> |

Skift alle 50 timer

**KØREREDUKTIONSENHEDER**  
Kapacitet: 0,9-1,1 liter (hvert)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2       |  |
|---------------------|---------------------------|--|
| <b>SP Gear 1011</b> | <b>Syngear TDL 75W-90</b> |  |

Skift alle 1000 timer/ 12 måneder

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2       |  |
|---------------------|---------------------------|--|
| <b>SP Gear 1011</b> | <b>Syngear TDL 75W-90</b> |  |

Skift alle 150 timer/ 4 måneder

**HYDRAULISK SYSTEM**

Kapacitet: 70 liter (Hydrauliksystem inkl. tank), Kapacitet: 41,6 liter (Hydrauliktank)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  |  |  |
|----------------------|--|--|
| <b>Perlus HCD 46</b> |  |  |

Skift alle 250 timer/ 6 måneder

| ANVEND                     | KLIMA   |
|----------------------------|---------|
| Biologisk nedbrydelig olie | Moderat |

| PRODUKTANBEFALING 1       |  |  |
|---------------------------|--|--|
| <b>Perlus Biosynth 46</b> |  |  |

Skift alle 250 timer/ 6 måneder

# GEHL LÆSSEMASKINERR MED KOMPAKT SPORVIDDE RT/CTL RT175 YANMAR 4TNV98-ZNMS TIER 4I (S/N 10721 - 811000)



## SMØREPUNKTER/NIPLER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## KØLESYSTEM

Kapacitet: 13,2 liter

| ANVEND                |                      | KLIMA                         |
|-----------------------|----------------------|-------------------------------|
| Normal                |                      | Moderat                       |
| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2  | PRODUKTANBEFALING 3           |
| <b>Coolant SP 15+</b> | <b>Coolant SP 12</b> | <b>Coolant -38 Organic NF</b> |

*Skift alle 500 timer/ 12 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*