

GEHL LÆSSERE, SKID-STEER R/SL/V R190 YANMAR 4TNV98C-NMS TIER 4I (2013 OG EFTER)



MOTOR Yanmar 4TNV98C
Kapacitet: 9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Skift alle 250 timer/ 6 måneder

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Skift alle 50 timer

HYDRAULISK SYSTEM

Kapacitet: 41,6 liter (Hydrauliksystem inkl. tank), Kapacitet: 30,3 liter (Hydrauliktank)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Perlus HCD 46		

Skift alle 500 timer/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 5,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Skift alle 1000 timer/ 12 måneder

GEHL LÆSSERE, SKID-STEER R/SL/V R190 YANMAR 4TNV98C-NMS TIER 4I (2013 OG EFTER)

**DRIVKÆDEHUS**

Kapacitet: 9 liter (hvert)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Multifleet SHPD 10W-40*Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

PRODUKTANBEFALING 3

Multifleet SHPD 10W-40*Skift alle 50 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.