

GEHL LÆSSERE, SKID-STEER R/SL/V V270 YANMAR 4TNV98T-TIER 3 (S/N 021601 ->) (2008-2011)



MOTOR Yanmar 4TNV98T

Kapacitet: 10,4 liter, Filterkapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 2

Agrisynth LSP 10W-40

PRODUKTANBEFALING 3

Agridiesel CRD+ 15W-40

Skift alle 250 timer/ 6 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 2

Agrisynth LSP 10W-40

PRODUKTANBEFALING 3

Agridiesel CRD+ 15W-40

Skift alle 50 timer

HYDRAULISK SYSTEM

Kapacitet: 39,7 liter (Hydrauliktank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus HCD 46

Skift alle 1000 timer/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 8,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 500 timer/ 12 måneder

GEHL LÆSSERE, SKID-STEER R/SL/V V270 **YANMAR 4TNV98T-TIER 3 (S/N 021601 ->)** **(2008-2011)**



KÆDEKASSE

Kapacitet: 9,5 liter (hver side)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

Kontroller alle 250 timer, skift alle 1000 timer/ 12 måneder

ANVEND

Første Service

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 15W-40

Skift alle 50 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.