

GENIE SAKSELIFTE, SELVSTYRENDE, HÅRDT TERRÆN GS-2668 RT KUBOTA D- 905, (101 - 41999) (KASSE 2007)



MOTOR Kubota D905
Kapacitet: 5,1 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 10 timer, skift alle 200 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 20W-20

Kontroller alle 10 timer, skift alle 200 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 200 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 10W

Kontroller alle 10 timer, skift alle 200 timer

ANVEND	KLIMA
Første Service	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 10 timer, skift alle 50 timer

ANVEND	KLIMA
Første Service	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 20W-20

Kontroller alle 10 timer, skift alle 50 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Kroontrak CVT 10W-40

PRODUKTANBEFALING 2

Agridiesel CRD+ 15W-40

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 50 timer

GENIE SAKSELIFTE, SELVSTYRENDE, HÅRDT TERRÆN GS-2668 RT KUBOTA D- 905, (101 - 41999) (KASSE 2007)



ANVEND		KLIMA
Første Service		Arktisk
PRODUKTANBEFALING 1		
Multifleet SCD 10W		
<i>Kontroller alle 10 timer, skift alle 50 timer</i>		

HYDRAULISK SYSTEM		
Kapacitet: 81,4 liter (Hydrauliktank), Kapacitet: 94,6 liter (Komplet)		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	
<i>Kontroller alle 250 timer, skift alle 2000 timer/ 24 måneder</i>		

SMØREPUNKTER/NIPLER		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM		
Kapacitet: 3,1 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	
<i>Kontroller alle 10 timer, skift alle 24 måneder</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.