

# GENIE SAKSELIFTE, SELVSTYRENDE, HÅRDT TERRÆN GS-3268 RT KUBOTA D- 1105 TIER 4, (42000 -) (2007 OG EFTER)



**MOTOR** Kubota D1105 Tier 4  
Kapacitet: 5,1 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Tropisk |

PRODUKTANBEFALING 1

**Multifleet SCD 30**

Kontroller alle 10 timer, skift alle 200 timer

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

PRODUKTANBEFALING 1

**Multifleet SCD 20W-20**

Kontroller alle 10 timer, skift alle 200 timer

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 2

**Asyntho 5W-30**

PRODUKTANBEFALING 3

**Armado Synth 5W-30**

Kontroller alle 10 timer, skift alle 200 timer

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Arktisk |

PRODUKTANBEFALING 1

**Multifleet SCD 10W**

Kontroller alle 10 timer, skift alle 200 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Tropisk |

PRODUKTANBEFALING 1

**Multifleet SCD 30**

Kontroller alle 10 timer, skift alle 50 timer

| ANVEND         | KLIMA            |
|----------------|------------------|
| Første Service | Middelhavsagtigt |

PRODUKTANBEFALING 1

**Multifleet SCD 20W-20**

Kontroller alle 10 timer, skift alle 50 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

PRODUKTANBEFALING 1

**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 2

**Asyntho 5W-30**

PRODUKTANBEFALING 3

**Armado Synth 5W-30**

Kontroller alle 10 timer, skift alle 50 timer

# GENIE SAKSELIFTE, SELVSTYRENDE, HÅRDT TERRÆN GS-3268 RT KUBOTA D- 1105 TIER 4, (42000 -) (2007 OG EFTER)



| ANVEND                                               |  | KLIMA   |
|------------------------------------------------------|--|---------|
| Første Service                                       |  | Arktisk |
| PRODUKTANBEFALING 1                                  |  |         |
| <b>Multifleet SCD 10W</b>                            |  |         |
| <i>Kontroller alle 10 timer, skift alle 50 timer</i> |  |         |

| HYDRAULISK SYSTEM                                                    |                     |         |
|----------------------------------------------------------------------|---------------------|---------|
| Kapacitet: 56,8 liter (Hydrauliktank), Kapacitet: 62 liter (Komplet) |                     |         |
| ANVEND                                                               |                     | KLIMA   |
| Normal                                                               |                     | Moderat |
| PRODUKTANBEFALING 1                                                  | PRODUKTANBEFALING 2 |         |
| <b>SP Matic 2032</b>                                                 | <b>ATF Almirol</b>  |         |
| <i>Kontroller alle 250 timer, skift alle 2000 timer/ 24 måneder</i>  |                     |         |

| SMØREPUNKTER/NIPLER  |                                 |                              |
|----------------------|---------------------------------|------------------------------|
| ANVEND               |                                 | KLIMA                        |
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

| KØLESYSTEM                                             |                     |         |
|--------------------------------------------------------|---------------------|---------|
| Kapacitet: 3,1 liter                                   |                     |         |
| ANVEND                                                 |                     | KLIMA   |
| Normal                                                 |                     | Moderat |
| PRODUKTANBEFALING 1                                    | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b>                          | <b>Coolant -26</b>  |         |
| <i>Kontroller alle 10 timer, skift alle 24 måneder</i> |                     |         |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.